Video description

Narration Text

Narrator. Title image with foam background.
Video of Rick Demmer mixing foam, glove boxes, contaminated structures, or contaminated sites.

The gelatin used in Jell-O is making a special contribution to cleaning buildings, equipment and structures at America's contaminated sites.

Rick Demmer, on camera, in lab and mixing and spraying foam.

"In thinking about DARPA's challenge to create innovative solutions for cleaning contaminated surfaces, our team needed a stable foam to keep the chemicals in place to do their work. After many tests, we discovered that gelatin, the main ingredient used in Jell-O worked well in making a proper foam."

Narrator.

Move to R. Demmer spraying foam, then to images of applying foam.

This discovery advanced INL's research efforts in creating Rad-Release, a two-part breakthrough that removes radioactive and concentrated metals from various surfaces.

Narrator.

DARPA and NHS logos, plus the RFP Notice

DARPA and the Department of
Homeland Security were seeking
innovative technologies in case of a
radioactive dispersal device
detonation.

Narrator.
Photo of team
Move to video of team in laboratory

Seven INL researchers responded,
perfecting a foam and clay
extraction process effective in
removing even the most radioactive
contaminants, including
transuranics.

Narrator.

Video of applying foam, then move to animation and graphic with 2 Parts listed: Part 1

- 1. Apply Foam
- 2. Vacuum Foam

Part 2

- 1. Apply Clay-Salt Combination
- 2. Remove, Package Clay for Disposal

Part 1 involves applying a specifically blended chemical foam to contaminated surfaces, then letting the reagent process work for two hours.

Narrator. R. Demmer vacuuming foam, then returning to animation of foam praocess.

Next, a vacuum is used to remove the foam taking with it at least 50 percent of the contaminants. If

additional decontamination is necessary, the second part of the technology is employed.

Narrator.

Karen Wright demonstrating Part 2 (Apply Clay-Salt application), then move to animation of part 2.

Part 2 involves applying wet clay saturated with potassium chloride to extract the contaminants hiding in the subsurface pores and capillaries. This process involves a slow mass transfer, where contaminant particles seek equilibrium by spreading from higher to lower concentrations in the clay.

Narrator. Return to clay application process, and spray application video.

This slow process takes two to six weeks, depending on the type of contaminant. For large application areas, clay can be sprayed on with commercial sprayers.

Narrator.

Back to animation with two parts noted, then to K. Wright removing clay.

Finally, clay with contaminants is removed and packaged for appropriate, safe disposal.

Narrator.

Animated charts of contaminant removal over time.

The application of Rad-Release foam can remove 50 percent of contamination in just two hours. If the clay is applied in addition to the foam, 80 percent can be removed in one day, 88 percent in one week, and 95 percent in six weeks.

Karen Wright on camera in lab. Move to field testing footage or still images. "Rad-Release has won several competitions, including an international contest against

German, British and Canadian technologies. It also removed 30-50 percent more contamination than the best technologies offered by

U.S. national laboratories and companies."

Narrator.

EPA logo, page one of the report.

EAI logo.

Move to footage or stills of decontamination activities, maybe some of Argonne or West Valley, NY.

In a 2010 EPA study, Rad-Release removed 71 percent of the contamination. Licensee Environmental Alternatives, Inc. has successfully removed up to 95 percent of contamination in glove boxes and hot cells at Argonne National Laboratory and West Valley, New York.

Narrator.

Return to R. Demmer applying foam. Then, graphic detailing benefits, quickly moving through each point

Rad-Release -

- Returns facilities to use,
- Is non-destructive
- Reduces processing costs,
- Uses inexpensive materials,
- Treats all radionuclides, including transuranics,
- Minimizes waste costs and volume, and
- Reduces worker exposure to contaminated materials.

Rad-Release removes 30-50 percent more contaminant than any other technology, but boasts a dozen or more advantages, including:

- Returns buildings, equipment and structures to use,
- Is non-destructive,
- · Reduces costs in processing,
- Uses inexpensive materials,
- Treats all radionuclides, including transuranics,
- Minimizes waste costs and volume, and

• Reduces worker exposure to contaminated materials.

Karen Wright on camera.

Rad-Release is a major breakthrough in cleaning up contaminated surfaces. It is effective and without a doubt has earned the designation as "The Reagent of Choice."

End Graphic: animated INL logo

END